



24" [600 mm] HDPE ACCESS PIPE REQUIRED.
USE FACTORY PRE-CORED END CAPS.

2 LAYERS OF AASHTO M288 CLASS 1 WOVEN GEOTEXTILE
BETWEEN FOUNDATION STONE AND CHAMBERS.
MC-3500 - 8.25' [2.51 m] WIDE STRIPS

NOTE: FOR MANY APPLICATIONS, THE NON-WOVEN GEOTEXTILE OVER THE MC-3500 CHAMBERS CAN BE ELIMINATED OR SUBSTITUTED WITH THE AASHTO CLASS 1 WOVEN GEOTEXTILE. CONTACT YOUR STORMTECH REPRESENTATIVE FOR ASSISTANCE.

STORMTECH STANDARD DETAIL DISCLAIMER

STORMTECH STANDARD DETAIL'S DEMONSTRATE RECOMMENDATIONS FOR INSTALLATION AND/OR STANDARD DIMENSIONS OF STORMTECH PRODUCTS. STORMTECH DETAILS DO NOT SUPERSEDE ANY STATE OR LOCAL REGULATORY SPECIFICATIONS. IT IS THE RESPONSIBILITY OF THE CONSULTING ENGINEER TO ENSURE COMPLIANCE WITH ALL REGULATORY SPECIFICATIONS. STORMTECH HAS NOT AUTHORIZED, AND IS NOT RESPONSIBLE FOR ANY ALTERATIONS BY OTHERS TO STORMTECH STANDARD DETAILS.



StormTech
Division of Watershed Management
 Subsurface Stormwater Management
 20 BEAVER ROAD, SUITE 104
 WETHERSFIELD, CT 06109
 PHONE: 866-892-2694
 FAX: 866-328-9401
 WWW.STORMTECH.COM

MC-3500 ISOLATOR™ ROW PROFILE

SCALE:	NTS
DATE:	7-17-09
DRAWN BY:	JLM
CHECKED:	